



# TTP-2410M vs. Competition

Model	TSC TTP-2410M	Zebra Z4Mplus	Datamax I-4210	TSC TTP-246M Plus	Zebra S4M
Printer Feature					
Print method	Thermal Transfer & Direct Thermal	Thermal Transfer & Direct Thermal	Thermal Transfer & Direct Thermal	Thermal Transfer & Direct Thermal	Direct Thermal & Thermal Transfer (optional)
<b>Specifications</b>					
Resolution	203 dpi	203 dpi	203 dpi	203 dpi	203dpi
Size(W*H*D)	*10.63**12.13**19.90"	10.93**13.32**18.69"	12.62**12.70**18.60"	*10.63**12.13**19.90"	10.7**11.6**18.8"
Print Speed	10" (245mm)/sec	10" (245mm)/sec	10" (245mm)/sec	6" (152.4mm)/sec	6" (152 mm)/sec
Print Width , max.	4.09" (104 mm)	4.09" (104 mm)	4.10" (104mm)	4.09" (104 mm)	4.09" (104 mm)
Label roll capacity	*8.2" OD	8" OD	8" OD	*8.2" OD	8" OD
Ribbon capacity	*600 M	450 M	600 M	*600 M	450 M
Memory	*32MB SDRAM / 8MB Flash SD flash memory card slot	8 MB RAM / 4MB Flash	16MB RAM / 2MB Flash	*8MB SDRAM / 4MB Flash SD flash memory card slot (Option)	8 MB RAM / 4 MB Flash
<b>Interface</b>					
Serial	Std	Std	Std	Std	Std
Parallel	Std	Std	Std	Std	Std
USB	*Std		Option	*Std	Option
<b>Options</b>					
Ethernet	Internal ethernet (Std)	Option	Option	Option	Option
Wireless	Option	Option		Option	Option
Peel-off	Std	Option	Option	Option	Option
Cutter	Option	Option	Option	Option	Option
RFID	*Option	R4M		*Option	
GPIO	*Option			*Option	