

Toshiba TEC Ribbon Saving Module

B-4905-R-QM

Warning

Disconnect the power cord before installing the Ribbon Saving Module

1. PACKING LIST

All the following parts are supplied with the kits. Make sure you have all items shown below.

Description	Q'ty/Unit
Ribbon Saving Module	1

2. INSTALLATION PROCEDURES

- STEP 1. Turn the head lever counterclockwise to release the ribbon shaft holder plate.
- STEP 2. Remove the ribbon stopper from the ribbon shaft on which the ribbon is wound. Before removing the ribbon stopper, check its attaching direction for later installation. Remove the ribbon stopper from the ribbon shaft on which the ribbon is wound.
- STEP 3. Remove the two SM-4 x 88 screws to detach the solenoid attaching plate.
- STEP 4. Pass the solenoid harness, of the ribbon saving module, through the opening from the print block side and connect to CN14 (B472) or CN12 (B572) on the CPU PC board. Fix the harness with the clamp.
- STEP 5. Install the ribbon saving module on the print block. STEP 6. Assemble the solenoid unit so that the head up link engages the spring pin. STEP 7. Secure the ribbon saving module with the SM-4 x 88 screws removed in STEP 3.
- STEP 8. Set the DIP SW 1-1 to ON.

NOTE: Make sure to remove any dust that appears during removal or installation because it may affect the print quality

CAUTION:

Take care to orient the screws so that they are vertically aligned with the ribbon saving module.